


* BACKFILL TO BE COMPACTED IN 8" LIFTS WITH NO STONES OVER 6" IN ANY DIMENSION.

TRENCH CROSS SECTION




SHRUB PLANTING DETAIL

GENERAL LANDSCAPING NOTES


- Double-dig all planting areas. Install 3" topsoil-compost mix.
- Install 3" bark mulch on all landscape beds and tree pits. Edge all beds by digging trench around outside edges.
- All plants shall conform to the latest issue of American Nurseryman Standards for Nursery Stock.
- 4. This drawing shall be used for landscaping purposes only.
- Install lawn on all disturbed areas except landscaped beds.

COPIES FROM THE ORIGINAL OF THIS DOCUMENT NOT MARKED WITH AN ORIGINAL OF THE PROFESSIONAL ENGINEER'S AND/OR LAND SURVEYOR'S STAMP OR EMBOSSED SEAL SHALL NOT BE CONSIDERED VALID, TRUE COPIES.


UNAUTHORIZED ALTERATION OR ADDITION TO THIS DOCUMENT IS A VIOLATION OF SECTION 7209-2 OF THE NEW YORK STATE EDUCATION LAW.



PARKING SPACE STRIPING DETAIL









SECTION - PARKING LOT PAVEMENT

NOT TO SCALE





PRE-CAST MANHOLE

NOT TO SCALE

- 1. SMOOTH CHANNEL INVERT TO BE PAVED WITH CEMENT MORTAR.
- 3. SANITARY SEWER TO EXTEND INTO THE MANHOLE ONLY TO A POINT WHERE OUTSIDE OF SEWER MEETS INSIDE WALL OF MANHOLE.

DETAILS

B - 03 - 0227- 02


Drawing No.:

33 - 2 - 3

N.T.S.

2 OF 2

- OPENING FOR PIPE SHALL BE PRE-CAST. CONNECTIONS TO EXISTING MANHOLES SHALL BE MACHINE CORED.
- 5. MANHOLE COVERS TO BE STAMPED "SANITARY".
- 6. PRECAST REINFORCED CONCRETE MANHOLE SHALL BE DESIGNED FOR H20 LIVE LOAD.



JQ